

**DESCRIPTION**

The VBP6324DN comes with a host of features to suit most applications; 3.8-9.5mm vari-focal lens, day/night function, service video output, as well as a Tri-axis mechanism for free lens rotation.

Operating in light levels as low as 0.3Lux during the daytime and 0.05Lux at night, the VBP6324DN provides the ideal solution for around the clock surveillance.

Whilst the VBP6324DN is ideal for ceiling mount installations, the tri axis mechanism allows free lens rotation making it particularly suitable for wall mounted applications as well




**KEY FEATURES**

- High Sensitivity 1/3" SONY Super HAD CCD
- Built-in DC Iris Vari-focal Lens, 550 TV Lines
- Min. Illumination: 0.3 Lux Colour, 0.05 B/W, Day&Night(ICR)
- AGC, BLC, Flickerless On/Off, Auto White Balance
- 100mm Dome Size
- 12V DC
- Service Video Output
- 3-Axis Mechanism for Free Lens Rotation


**5 Year Warranty**




**Service Video Output**  
Enables test monitor to be connected direct to camera



Pan Rotation



Tilt Rotation



Horizontal Rotation

## TECHNICAL SPECIFICATION

Scanning System	625 Lines 2:1 Interlace
Sync. System	Internal
Image Sensor	1/3 inch SONY Super HAD CCD
Total/Effective Pixels	470K/440K
Lens	DC Iris Vari-focal Lens (f=3.8~9.5mm)
Horizontal Resolution	550 TV Lines
Video S/N Ratio	More than 48dB (AGC Off)
Min. Illumination	Color (0.3 Lux, DSS), B/W (0.05 Lux)
Electronic Shutter	1/50 ~ 1/10,000 sec.
White Balance	Auto
AGC	On/Off
Back Light Compensation	On/Off
Flickerless	On/Off
Service Video Output	Yes
Day&Night (ICR)	Auto/Day/Night
Power	DC 12V (9V ~ 15V)
Dimensions	100(Ø) x 102.0(D) mm

[www.videcon.co.uk](http://www.videcon.co.uk)

Vision House, High Street,  
Heckmondwike, West Yorkshire  
WF16 OAD UK

Tel +44 (0) 1924 528000  
Fax +44(0) 1924 528005  
E-mail [sales@videcon.co.uk](mailto:sales@videcon.co.uk)